



# INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT

*We make Indiana a cleaner, healthier place to live.*

Frank O'Bannon  
Governor

Lori F. Kaplan  
Commissioner

June 18, 2003

100 North Senate Avenue  
P. O. Box 6015  
Indianapolis, Indiana 46206-6015  
(317) 232-8603  
(800) 451-6027  
www.IN.gov/idem

TO: Interested Parties / Applicant

RE: Auburn Foundry, Inc. Plant #1  
#033-17306-00002

FROM: Paul Dubenetzky  
Chief, Permits Branch  
Office of Air Quality

## Notice of Decision: Approval - Effective Immediately

Please be advised that on behalf of the Commissioner of the Department of Environmental Management, I have issued a decision regarding the enclosed matter. Pursuant to IC 13-17-3-4 and 326 IAC 2, this approval is effective immediately, unless a petition for stay of effectiveness is filed and granted, and may be revoked or modified in accordance with the provisions of IC 13-15-7-1.

If you wish to challenge this decision, IC 4-21.5-3-7 require that you file a petition for administrative review. This petition may include a request for stay of effectiveness and must be submitted to the Office of Environmental Adjudication, ISTA Building, 150 W. Market Street, Suite 618, Indianapolis, IN 46204, **within (18) eighteen days of the mailing of this notice**. The filing of a petition for administrative review is complete on the earliest of the following dates that apply to the filing:

- (1) the date the document is delivered to the Office of Environmental Adjudication (OEA);
- (2) the date of the postmark on the envelope containing the document, if the document is mailed to OEA by U.S. mail; or
- (3) the date on which the document is deposited with a private carrier, as shown by receipt issued by the carrier, if the document is sent to the OEA by private carrier.

The petition must include facts demonstrating that you are either the applicant, a person aggrieved or adversely affected by the decision or otherwise entitled to review by law. Please identify the permit, decision, or other order for which you seek review by permit number, name of the applicant, location, date of this notice and all of the following:

- (1) the name and address of the person making the request;
- (2) the interest of the person making the request;
- (3) identification of any persons represented by the person making the request;
- (4) the reasons, with particularity, for the request;
- (5) the issues, with particularity, proposed for consideration at any hearing; and
- (6) identification of the terms and conditions which, in the judgment of the person making the request, would be appropriate in the case in question to satisfy the requirements of the law governing documents of the type issued by the Commissioner.

If you have technical questions regarding the enclosed documents, please contact the Office of Air Quality, Permits Branch at (317) 233-0178. Callers from within Indiana may call toll-free at 1-800-451-6027, ext. 3-0178.

Enclosure

FNPERMOD.wpd 8/21/02

# **PART 70 MINOR SOURCE MODIFICATION OFFICE OF AIR QUALITY**

**Auburn Foundry, Inc. Plant #1  
635 West 11<sup>th</sup> Street  
Auburn, Indiana 46706**

(herein known as the Permittee) is hereby authorized to construct and operate subject to the conditions contained herein, the emission units described in Section A (Source Summary) of this approval.

This approval is issued in accordance with 326 IAC 2 and 40 CFR Part 70 Appendix A and contains the conditions and provisions specified in 326 IAC 2-7 as required by 42 U.S.C. 7401, et. seq. (Clean Air Act as amended by the 1990 Clean Air Act Amendments), 40 CFR Part 70.6, IC 13-15 and IC 13-17.

Source Modification No.: 033-17306-00002	
Issued by:Original Signed by Paul Dubenetzky, Branch Chief Office of Air Quality	Issuance Date: June 18, 2003

## TABLE OF CONTENTS

<b>A</b>	<b>SOURCE SUMMARY</b>	<b>3</b>
A.1	General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]	
A.2	Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)]	
A.3	Part 70 Permit Applicability [326 IAC 2-7-2]	
<b>B</b>	<b>GENERAL CONSTRUCTION CONDITIONS</b>	<b>4</b>
B.1	Definitions [326 IAC 2-7-1]	
B.2	Effective Date of the Permit [IC13-15-5-3]	
B.3	Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]	
<b>C</b>	<b>GENERAL OPERATION CONDITIONS</b>	<b>5</b>
C.1	Certification [326 IAC 2-7-4(f)] [326 IAC 2-7-6(1)][326 IAC 2-7-5(3)(C)]	
C.2	Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)]	
C.3	Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]	
C.4	Opacity [326 IAC 5-1]	
C.5	Fugitive Dust Emissions [326 IAC 6-4]	
C.6	Fugitive Dust Emissions [326 IAC 6-1-11.1]	
C.7	Operation of Equipment [326 IAC 2-7-6(6)]	
C.8	Stack Height [326 IAC 1-7]	
C.9	Performance Testing [326 IAC 3-6][326 IAC 2-1.1-11]	
C.10	Compliance Requirements [326 IAC 2-1.1-11]	
C.11	Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]	
C.12	Maintenance of Monitoring Equipment [326 IAC 2-7-5(3)(A)(iii)]	
C.13	Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]	
C.14	Pressure Gauge and Other Instrument Specifications	
C.15	Compliance Response Plan - Preparation, Implementation, Records, and Reports	
C.16	Emergency Provisions	
C.17	Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5]	
C.18	General Record Keeping Requirements [326 IAC 2-7-5(3)]	
C.19	General Reporting Requirements [326 IAC 2-7-5(3)(C)]	
C.20	Relocation of Portable Sources [326 IAC 2-14-4]	
<b>D.1</b>	<b>FACILITY OPERATION CONDITIONS</b>	<b>12</b>
D.1.1	Source Modifications 326 IAC 2-7-10.5	
D.1.2	Particulate Matter (PM) [326 IAC 2-2]	
D.1.3	Particulate [326 IAC 6-3-2]	
D.1.4	Preventive Maintenance Plan [326 IAC 2-7-5(13)]	
D.1.5	Testing requirement	
D.1.6	Particulate Control	
D.1.7	Visible Emissions Notations	
D.1.8	Parametric Monitoring	
D.1.9	Baghouse Inspections	
D.1.10	Broken or Failed Bag Detection	
D.1.11	Record Keeping Requirements	
D.1.12	Reporting Requirements	
	<b>Certification</b>	<b>16</b>
	<b>Quarterly Report</b>	<b>17</b>

## SECTION A

## SOURCE SUMMARY

This approval is based on information requested by the Indiana Department of Environmental Management (IDEM), Office of Air Quality (OAQ). The information describing the emission units contained in conditions A.1 through A.2 is descriptive information and does not constitute enforceable conditions. However, the Permittee should be aware that a physical change or a change in the method of operation that may render this descriptive information obsolete or inaccurate may trigger requirements for the Permittee to obtain additional permits or seek modification of this approval pursuant to 326 IAC 2, or change other applicable requirements presented in the permit application.

### A.1 General Information [326 IAC 2-7-4(c)] [326 IAC 2-7-5(15)]

---

The Permittee owns and operates a gray iron foundry

Responsible Official:	Dave Webber, Vice President
Source Address:	635 West 11 <sup>th</sup> Street, Auburn, Indiana 46706
Mailing Address:	635 West 11 <sup>th</sup> Street, Auburn, Indiana 46706
General Source Phone Number:	260-925-0900
SIC Code:	3321
County Location:	DeKalb
Source Location Status:	Attainment for all criteria pollutants
Source Status:	Part 70 Permit Program Major Source, under PSD; Major Source, Section 112 of the Clean Air Act 1 of 28 Source Categories

### A.2 Emission Units and Pollution Control Equipment Summary [326 IAC 2-7-4(c)(3)] [326 IAC 2-7-5(15)]

---

This stationary source is approved to construct and operate the following emission units and pollution control devices:

One (1) Ductile Iron Conversion (DIC) station, identified as emission unit E-40, with a maximum capacity of 12 tons of metal per year, using baghouse BH-20 as control, and exhausting to stack 20.

### A.3 Part 70 Permit Applicability [326 IAC 2-7-2]

---

This stationary source is required to have a Part 70 permit by 326 IAC 2-7-2 (Applicability) because: .

- (a) It is a major source, as defined in 326 IAC 2-7-1(22);
- (b) It is a source in a source category designated by the United States Environmental Protection Agency (U.S. EPA) under 40 CFR 70.3 (Part 70 - Applicability).

## **SECTION B                      GENERAL CONSTRUCTION CONDITIONS**

### **B.1       Definitions [326 IAC 2-7-1]**

---

Terms in this permit shall have the definition assigned to such terms in the referenced regulation. In the absence of definitions in the referenced regulation, the applicable definitions found in the statutes or regulations (IC 13-11, 326 IAC 1-2 and 326 IAC 2-7) shall prevail.

### **B.2       Effective Date of the Permit [IC13-15-5-3]**

---

Pursuant to IC 13-15-5-3, this approval becomes effective upon its issuance.

### **B.3       Revocation of Permits [326 IAC 2-1.1-9(5)][326 IAC 2-7-10.5(i)]**

---

Pursuant to 326 IAC 2-1.1-9(5)(Revocation of Permits), the Commissioner may revoke this approval if construction is not commenced within eighteen (18) months after receipt of this approval or if construction is suspended for a continuous period of one (1) year or more.

## SECTION C GENERAL OPERATION CONDITIONS

### C.1 Certification ~~[326 IAC 2-7-4(f)]~~~~[326 IAC 2-7-6(1)]~~~~[326 IAC 2-7-5(3)(C)]~~

---

- (a) Where specifically designated by this permit or required by an applicable requirement, any application form, report, or compliance certification submitted shall contain certification by a responsible official of truth, accuracy, and completeness. This certification shall state that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.
- (b) One (1) certification shall be included, using the attached Certification Form, with each submittal requiring certification.
- (c) A responsible official is defined at 326 IAC 2-7-1(34).

### C.2 Preventive Maintenance Plan [326 IAC 2-7-5(1),(3) and (13)] [326 IAC 2-7-6(1) and (6)] ~~[326 IAC 1-6-3]~~

---

- (a) If required by specific condition(s) in Section D of this permit, the Permittee shall prepare and maintain Preventive Maintenance Plans (PMPs) when operation begins, including the following information on each facility:
  - (1) Identification of the individual(s) responsible for inspecting, maintaining, and repairing emission control devices;
  - (2) A description of the items or conditions that will be inspected and the inspection schedule for said items or conditions; and
  - (3) Identification and quantification of the replacement parts that will be maintained in inventory for quick replacement.

If, due to circumstances beyond the Permittee's control, the PMPs cannot be prepared and maintained within the above time frame, the Permittee may extend the date an additional ninety (90) days provided the Permittee notifies:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

The PMP and the PMP extension notification do not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall implement the PMPs as necessary to ensure that failure to implement a PMP does not cause or contribute to a violation of any limitation on emissions or potential to emit.
- (c) A copy of the PMPs shall be submitted to IDEM, OAQ, upon request and within a reasonable time, and shall be subject to review and approval by IDEM, OAQ. IDEM, OAQ, may require the Permittee to revise its PMPs whenever lack of proper maintenance causes or contributes to any violation. The PMP does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) Records of preventive maintenance shall be retained for a period of at least five (5) years. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the

Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.

**C.3 Permit Amendment or Modification [326 IAC 2-7-11] [326 IAC 2-7-12]**

---

(a) Permit amendments and modifications are governed by the requirements of 326 IAC 2-7-11 or 326 IAC 2-7-12 whenever the Permittee seeks to amend or modify this permit.

(b) Any application requesting an amendment or modification of this permit shall be submitted to:

Indiana Department of Environmental Management  
Permits Branch, Office of Air Quality  
100 North Senate Avenue, P.O. Box 6015  
Indianapolis, Indiana 46206-6015

Any such application shall be certified by the "responsible official" as defined by 326 IAC 2-7-1(34).

(c) The Permittee may implement administrative amendment changes addressed in the request for an administrative amendment immediately upon submittal of the request. [326 IAC 2-7-11(c)(3)]

**C.4 Opacity [326 IAC 5-1]**

---

Pursuant to 326 IAC 5-1-2 (Opacity Limitations), except as provided in 326 IAC 5-1-3 (Temporary Alternative Opacity Limitations), opacity shall meet the following, unless otherwise stated in this permit:

(a) Opacity shall not exceed an average of forty percent (40%) in any one (1) six (6) minute averaging period as determined in 326 IAC 5-1-4.

(b) Opacity shall not exceed sixty percent (60%) for more than a cumulative total of fifteen (15) minutes (sixty (60) readings as measured according to 40 CFR 60, Appendix A, Method 9 or fifteen (15) one (1) minute nonoverlapping integrated averages for a continuous opacity monitor) in a six (6) hour period.

**C.5 Fugitive Dust Emissions [326 IAC 6-4]**

---

The Permittee shall not allow fugitive dust to escape beyond the property line or boundaries of the property, right-of-way, or easement on which the source is located, in a manner that would violate 326 IAC 6-4 (Fugitive Dust Emissions).

**C.6 Operation of Equipment [326 IAC 2-7-6(6)]**

---

Except as otherwise provided by statute or rule, or in this permit, all air pollution control equipment listed in this permit and used to comply with an applicable requirement shall be operated at all times that the emission unit vented to the control equipment is in operation.

**C.7 Stack Height [326 IAC 1-7]**

---

The Permittee shall comply with the applicable provisions of 326 IAC 1-7 (Stack Height Provisions), for all exhaust stacks through which a potential (before controls) of twenty-five (25) tons per year or more of particulate matter or sulfur dioxide is emitted by using good engineering practices (GEP) pursuant to 326 IAC 1-7-3.

## **Testing Requirements [326 IAC 2-7-6(1)]**

### **C.9 Performance Testing [326 IAC 3-6][326 IAC 2-1.1-11]**

---

- (a) Compliance testing on new emission units shall be conducted within 60 days after achieving maximum production rate, but no later than 180 days after initial start-up, if specified in Section D of this approval. All testing shall be performed according to the provisions of 326 IAC 3-6 (Source Sampling Procedures), except as provided elsewhere in this approval, utilizing any applicable procedures and analysis methods specified in 40 CFR 51, 40 CFR 60, 40 CFR 61, 40 CFR 63, 40 CFR 75, or other procedures approved by IDEM, OAQ.

A test protocol, except as provided elsewhere in this approval, shall be submitted to:

Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

no later than thirty-five (35) days prior to the intended test date. The protocol submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (b) The Permittee shall notify IDEM, OAQ of the actual test date at least fourteen (14) days prior to the actual test date. The notification submitted by the Permittee does not require certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (c) Pursuant to 326 IAC 3-6-4(b), all test reports must be received by IDEM, OAQ not later than forty-five (45) days after the completion of the testing. An extension may be granted by IDEM, OAQ if the source submits to IDEM, OAQ, a reasonable written explanation not later than five (5) days prior to the end of the initial forty-five (45) day period.

## **Compliance Requirements [326 IAC 2-1.1-11]**

### **C.10 Compliance Requirements [326 IAC 2-1.1-11]**

---

The commissioner may require stack testing, monitoring, or reporting at any time to assure compliance with all applicable requirements. Any monitoring or testing shall be performed in accordance with 326 IAC 3 or other methods approved by the commissioner or the U. S. EPA.

## **Compliance Monitoring Requirements [326 IAC 2-7-5(1)] [326 IAC 2-7-6(1)]**

### **C.11 Compliance Monitoring [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

---

If required by Section D, all monitoring and record keeping requirements shall be implemented when operation begins. The Permittee shall be responsible for installing any necessary equipment and initiating any required monitoring related to that equipment.

### **C.13 Monitoring Methods [326 IAC 3] [40 CFR 60] [40 CFR 63]**

---

Any monitoring or testing required by Section D of this permit shall be performed according to the provisions of 326 IAC 3, 40 CFR 60, Appendix A, 40 CFR 60 Appendix B, 40 CFR 63, or other approved methods as specified in this permit.

### **C.14 Pressure Gauge [326 IAC 2-1.1-11] [326 IAC 2-7-5(3)] [326 IAC 2-7-6(1)]**

---

- (a) Whenever a condition in this permit requires the measurement of pressure drop across any part of the unit or its control device, the gauge employed shall have a scale such that the expected normal reading shall be no less than twenty percent (20%) of full scale and



be accurate within plus or minus two percent ( $\pm 2\%$ ) of full scale reading.

- (b) The Permittee may request the IDEM, OAQ approve the use of a pressure gauge or other instrument that does not meet the above specifications provided the Permittee can demonstrate an alternative pressure gauge or other instrument specification will adequately ensure compliance with permit conditions requiring the measurement of pressure drop or other parameters.

**Corrective Actions and Response Steps [326 IAC 2-7-5] [326 IAC 2-7-6]**

**C.15 Compliance Response Plan - Preparation, Implementation, Records, and Reports[326 IAC 2-7-5]  
[326 IAC 2-7-6]**

---

- (a) The Permittee is required to prepare a Compliance Response Plan (CRP) for each compliance monitoring condition of this permit. A CRP shall be submitted to IDEM, OAQ upon request. The CRP shall be prepared within ninety (90) days after issuance of this permit by the Permittee, supplemented from time to time by the Permittee, maintained on site, and comprised of:
  - (1) Reasonable response steps that may be implemented in the event that a response step is needed pursuant to the requirements of Section D of this permit; and an expected time frame for taking reasonable response steps.
  - (2) If, at any time, the Permittee takes reasonable response steps that are not set forth in the Permittee's current Compliance Response Plan and the Permittee documents such response in accordance with subsection (e) below, the Permittee shall amend its Compliance Response Plan to include such response steps taken.
- (b) For each compliance monitoring condition of this permit, reasonable response steps shall be taken when indicated by the provisions of that compliance monitoring condition as follows:
  - (1) Reasonable response steps shall be taken as set forth in the Permittee's current Compliance Response Plan; or
  - (2) If none of the reasonable response steps listed in the Compliance Response Plan is applicable or responsive to the excursion, the Permittee shall devise and implement additional response steps as expeditiously as practical. Taking such additional response steps shall not be considered a deviation from this permit so long as the Permittee documents such response steps in accordance with this condition.
  - (4) If the Permittee determines that additional response steps would necessitate that the emissions unit or control device be shut down, the IDEM, OAQ shall be promptly notified of the expected date of the shut down, the status of the applicable compliance monitoring parameter with respect to normal, and the results of the actions taken up to the time of notification.
  - (5) Failure to take reasonable response steps shall constitute a violation of the permit.
- (c) The Permittee is not required to take any further response steps for any of the following reasons:

- (1) A false reading occurs due to the malfunction of the monitoring equipment and prompt action was taken to correct the monitoring equipment.
  - (2) The Permittee has determined that the compliance monitoring parameters established in the permit conditions are technically inappropriate, has previously submitted a request for a minor permit modification to the permit, and such request has not been denied.
  - (3) An automatic measurement was taken when the process was not operating.
  - (4) The process has already returned or is returning to operating within "normal" parameters and no response steps are required.
- (d) When implementing reasonable steps in response to a compliance monitoring condition, if the Permittee determines that an exceedance of an emission limitation has occurred, the Permittee shall report such deviations pursuant to Section B-Deviations from Permit Requirements and Conditions.
- (e) The Permittee shall record all instances when response steps are taken. In the event of an emergency, the provisions of 326 IAC 2-7-16 (Emergency Provisions) requiring prompt corrective action to mitigate emissions shall prevail.
- (f) Except as otherwise provided by a rule or provided specifically in Section D, all monitoring as required in Section D shall be performed when the emission unit is operating, except for time necessary to perform quality assurance and maintenance activities.

C.16 Emergency Provisions [326 IAC 2-7-16]

- 
- (a) An emergency, as defined in 326 IAC 2-7-1(12), is not an affirmative defense for an action brought for noncompliance with a federal or state health-based emission limitation.
- (b) An emergency, as defined in 326 IAC 2-7-1(12), constitutes an affirmative defense to an action brought for noncompliance with a technology-based emission limitation if the affirmative defense of an emergency is demonstrated through properly signed, contemporaneous operating logs or other relevant evidence that describe the following:
- (1) An emergency occurred and the Permittee can, to the extent possible, identify the causes of the emergency;
  - (2) The permitted facility was at the time being properly operated;
  - (3) During the period of an emergency, the Permittee took all reasonable steps to minimize levels of emissions that exceeded the emission standards or other requirements in this permit;
  - (4) For each emergency lasting one (1) hour or more, the Permittee notified IDEM, OAQ and Northern Regional Office within four (4) daytime business hours after the beginning of the emergency, or after the emergency was discovered or reasonably should have been discovered;

Telephone Number: 1-800-451-6027 (ask for Office of Air Quality, Compliance Section), or  
Telephone Number: 317-233-5674 (ask for Compliance Section)

Facsimile Number: 317-233-5967

Northern Regional Office:  
Phone number: 219-245-4870  
Facsimile Numbers: 219-245-4877

- (5) For each emergency lasting one (1) hour or more, the Permittee submitted the attached Emergency Occurrence Report Form or its equivalent, either by mail or facsimile to:

Indiana Department of Environmental Management  
Compliance Branch, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015

within two (2) working days of the time when emission limitations were exceeded due to the emergency.

The notice fulfills the requirement of 326 IAC 2-7-5(3)(C)(ii) and must contain the following:

- (A) A description of the emergency;
- (B) Any steps taken to mitigate the emissions; and
- (C) Corrective actions taken.

The notification which shall be submitted by the Permittee does not require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

- (6) The Permittee immediately took all reasonable steps to correct the emergency.
- (c) In any enforcement proceeding, the Permittee seeking to establish the occurrence of an emergency has the burden of proof.
  - (d) This emergency provision supersedes 326 IAC 1-6 (Malfunctions). This permit condition is in addition to any emergency or upset provision contained in any applicable requirement.
  - (e) IDEM, OAQ, may require that the Preventive Maintenance Plans required under 326 IAC 2-7-4-(c)(10) be revised in response to an emergency.
  - (f) Failure to notify IDEM, OAQ, by telephone or facsimile of an emergency lasting more than one (1) hour in accordance with (b)(4) and (5) of this condition shall constitute a violation of 326 IAC 2-7 and any other applicable rules.
  - (g) If the emergency situation causes a deviation from a technology-based limit, the Permittee may continue to operate the affected emitting facilities during the emergency provided the Permittee immediately takes all reasonable steps to correct the emergency and minimize emissions.

C.17 Actions Related to Noncompliance Demonstrated by a Stack Test [326 IAC 2-7-5][326 IAC 2-7-6]

- (a) When the results of a stack test performed in conformance with Section C - Performance Testing, of this permit exceed the level specified in any condition of this permit, the

Permittee shall take appropriate response actions. The Permittee shall submit a description of these response actions to IDEM, OAQ, within thirty (30) days of receipt of the test results. The Permittee shall take appropriate action to minimize excess emissions from the affected facility while the response actions are being implemented.

- (b) A retest to demonstrate compliance shall be performed within one hundred twenty (120) days of receipt of the original test results. Should the Permittee demonstrate to IDEM, OAQ that retesting in one-hundred and twenty (120) days is not practicable, IDEM, OAQ may extend the retesting deadline.
- (c) IDEM, OAQ reserves the authority to take any actions allowed under law in response to noncompliant stack tests.

The documents submitted pursuant to this condition do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).

#### **Record Keeping and Reporting Requirements [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

##### **C.18 General Record Keeping Requirements [326 IAC 2-7-5(3)][326 IAC 2-7-6]**

- (a) Records of all required data, reports and support information shall be retained for a period of at least five (5) years from the date of monitoring sample, measurement, report, or application. These records shall be kept at the source location for a minimum of three (3) years. The records may be stored elsewhere for the remaining two (2) years as long as they are available upon request. If the Commissioner makes a request for records to the Permittee, the Permittee shall furnish the records to the Commissioner within a reasonable time.
- (b) Unless otherwise specified in this permit, all record keeping requirements not already legally required shall be implemented within ninety (90) days of permit issuance.

##### **C.19 General Reporting Requirements [326 IAC 2-7-5(3)(C)]**

- (a) The reports required by conditions in Section D of this permit shall be submitted to:  
  
Indiana Department of Environmental Management  
Compliance Data Section, Office of Air Quality  
100 North Senate Avenue, P. O. Box 6015  
Indianapolis, Indiana 46206-6015
- (b) Unless otherwise specified in this permit, any notice, report, or other submission required by this permit shall be considered timely if the date postmarked on the envelope or certified mail receipt, or affixed by the shipper on the private shipping receipt, is on or before the date it is due. If the document is submitted by any other means, it shall be considered timely if received by IDEM, OAQ, on or before the date it is due.
- (c) Unless otherwise specified in this permit, all reports required in Section D of this permit shall be submitted within thirty (30) days of the end of the reporting period. All reports do require the certification by the "responsible official" as defined by 326 IAC 2-7-1(34).
- (d) The first report shall cover the period commencing on the date of issuance of this permit and ending on the last day of the reporting period. Reporting periods are based on calendar years.

## SECTION D.1 FACILITY OPERATION CONDITIONS

### Facility Description [326 IAC 2-7-5(15)]

One (1) Ductile Iron Conversion (DIC) Station, identified as emission unit E-40, with a maximum capacity of 12 tons of metal per year, using baghouse BH-20 as control, and exhausting to stack 20.

(The information describing the process contained in this facility description box is descriptive information and does not constitute enforceable conditions.)

### Emission Limitations and Standards [326 IAC 2-7-5(1)]

#### D.1.1 Source Modifications 326 IAC 2-7-10.5

Pursuant to 326 IAC 2-7-10.5(d)(5)(C), the following conditions shall apply:

- (a) Baghouse BH-20 controlling the Ductile Iron Conversion (DIC) Station shall achieve and maintain ninety-nine percent (99%) control efficiency. In order to achieve this limit, the PM emission rate from the control device shall not exceed 0.216 pounds per hour.
- (b) Baghouse BH-20 controlling the Ductile Iron Conversion (DIC) Station shall comply with a no visible emission standard.
- (c) The potential to emit before controls shall not exceed major source thresholds for federal permitting programs.
- (d) The Permittee shall certify to the commissioner that the control device supplier guarantees that a specific outlet concentration, in conjunction with design air flow, will result in actual emissions less than twenty-five (25) tons of particulate matter (PM) or fifteen (15) tons per year of particulate matter with an aerodynamic diameter less than or equal to ten (10) micrometers ( $PM_{10}$ ).

#### D.1.2 Particulate Matter (PM) [326 IAC 2-2]

In order to render the requirements of 326 IAC 2-2 (PSD) not applicable to this modification, the total melt rate of the plant shall not exceed 208,463 tons per 12 consecutive month period with compliance determined at the end of each month. The limit on the plantwide melting rate will ensure that there will be no net increase in actual emissions from the rest of the foundry processes as a result of this modification.

#### D.1.3 Particulate [326 IAC 6-3-2]

Pursuant to 326 IAC 6-3-2 (Particulate Emission Limitations for Manufacturing Processes), the allowable particulate emission rate from the Ductile Iron Conversion (DIC) Station shall not exceed 21.7 pounds per hour when operating at a process weight rate of 12 tons per hour. The pounds per hour limitation was calculated using the following equation:

Interpolation of the data for the process weight rate up to 60,000 pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour; and} \\ P = \text{process weight rate in tons per hour}$$

#### D.1.4 Preventive Maintenance Plan [326 IAC 2-7-5(13)]

A Preventive Maintenance Plan, in accordance with Section C - Preventive Maintenance Plan, of this permit, is required for this facility and its control device.

## **Compliance Determination Requirements**

### **D.1.5 Testing requirement**

---

The permittee shall perform PM and opacity testing on the baghouse stack within 180 days after starting the operation of the new Ductile Iron Conversion (DIC) Station utilizing methods as approved by the Commissioner. Testing shall be conducted in accordance with Section C- Performance Testing. The test shall be performed to determine compliance with condition D.1.1(a) and D.1.(b).

### **D.1.6 Particulate Control**

---

To comply with the requirements of Condition D.1.1, baghouse BH-20 controlling the Ductile Iron Conversion (DIC) Station shall be in operation at all times when the Ductile Iron Conversion (DIC) Station is in operation.

## **Compliance Monitoring Requirements [326 IAC 2-7-6(1)] [326 IAC 2-7-5(1)]**

### **D.1.7 Visible Emissions Notations**

---

- (a) Visible emission notations of the Ductile Iron Conversions (DIC) Station stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (b) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (c) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (d) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (e) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

### **D.1.8 Parametric Monitoring**

---

The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the Ductile Iron Conversions (DIC) Station, at least once per shift when the Ductile Iron Conversions (DIC) Station is in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge and Other Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ, and shall be calibrated at least once every six (6) months.

#### **D.1.9 Baghouse Inspections**

---

An inspection shall be performed each calendar quarter of all bags controlling the Ductile Iron Conversions (DIC) Station when venting to the atmosphere. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

#### **D.1.10 Broken or Failed Bag Detection**

---

In the event that bag failure has been observed:

- (a) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (b) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

### **Record Keeping and Reporting Requirement [326 IAC 2-7-5(3)] [326 IAC 2-7-19]**

#### **D.1.11 Record Keeping Requirements**

---

- (a) To document compliance with condition D.1.2, the permittee shall maintain records of total metal melted at plant #1 each month.
- (b) To document compliance with Condition D.1.7, the Permittee shall maintain records of visible emission notations of the Ductile Iron Conversions (DIC) Station stack exhaust once per shift.
- (c) To document compliance with Condition D.1.8, the Permittee shall maintain records once per shift of the total static pressure drop during normal operation.
- (d) To document compliance with Condition D.1.9, the Permittee shall maintain records of the results of the inspections required under Condition D.1.9.
- (e) All records shall be maintained in accordance with Section C - General Record Keeping Requirements, of this permit.

#### **D.1.12 Reporting Requirements**

---

A quarterly summary of the information to document compliance with Condition D.1.2 shall be submitted to the address listed in Section C - General Reporting Requirements, of this permit, using the reporting forms located at the end of this permit, or their equivalent, within thirty (30) days after the end of the quarter being reported. The report submitted by the Permittee does

require the certification by the “responsible official” as defined by 326 IAC 2-7-1(34).



## INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT OFFICE OF AIR QUALITY

### PART 70 SOURCE MODIFICATION CERTIFICATION

Source Name: Auburn Foundry, Inc. Plant #1  
Source Address: 635 W. 11<sup>th</sup> St. Auburn, IN 46706  
Mailing Address: 635 W. 11<sup>th</sup> St. Auburn, IN 46706  
Source Modification No.: 033-17306-00002

**This certification shall be included when submitting monitoring, testing reports/results or other documents as required by this approval.**

Please check what document is being certified:

- 9 Test Result (specify) \_\_\_\_\_
- 9 Report (specify) \_\_\_\_\_
- 9 Notification (specify) \_\_\_\_\_
- 9 Affidavit (specify) \_\_\_\_\_
- 9 Other (specify) \_\_\_\_\_

I certify that, based on information and belief formed after reasonable inquiry, the statements and information in the document are true, accurate, and complete.

Signature:

Printed Name:

Title/Position:

Date:

**INDIANA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT  
OFFICE OF AIR QUALITY  
COMPLIANCE DATA SECTION**

**Part 70 Source Modification Quarterly Report**

Source Name: Auburn Foundry, Inc. Plant #1  
Source Address: 635 W. 11<sup>th</sup> St. Auburn, IN 46706  
Mailing Address: 635 W. 11<sup>th</sup> St. Auburn, IN 46706  
Source Modification No.: 033-17306-00002  
Facility: Plant wide  
Parameter: Metal Melted  
Limit: 208,463 tons per 12 consecutive month period with compliance determined at the end of each month

YEAR: \_\_\_\_\_

Month	Column 1	Column 2	Column 1 + Column 2
	This Month	Previous 11 Months	12 Month Total
Month 1			
Month 2			
Month 3			

9 No deviation occurred in this quarter.

9 Deviation/s occurred in this quarter.  
Deviation has been reported on: \_\_\_\_\_

Submitted by: \_\_\_\_\_  
Title / Position: \_\_\_\_\_  
Signature: \_\_\_\_\_  
Date: \_\_\_\_\_  
Phone: \_\_\_\_\_

Attach a signed certification to complete this report.

## Indiana Department of Environmental Management Office of Air Quality

### Technical Support Document (TSD) for a Part 70 Minor Source Modification.

#### Source Background and Description

Source Name: Auburn Foundry, Inc. Plant #1  
Source Location: 635 W. 11<sup>th</sup> St. Auburn, IN 46706  
County: DeKalb  
SIC Code: 3365  
Operation Permit No.: T 033-5978-00002  
Operation Permit Issuance Date: Not Yet Issued  
Minor Source Modification No.: 033-17306-00002  
Permit Reviewer: Ghassan Shalabi

The Office of Air Quality (OAQ) has reviewed a modification application from Auburn Foundry, Inc. Plant #1 relating to the construction of the following emission unit and pollution control devices:

One (1) Ductile Iron Conversion (DIC) Station, identified as emission unit E-40, with a maximum capacity of 12 tons of metal per hour, using baghouse BH-20 as control, and exhausting to stack 20.

#### History

On May 19, 2003, Auburn Foundry, Inc. Plant #1 submitted an application to the OAQ requesting to add a new Ductile Iron Conversion (DIC) Station at Plant #1 facility in Auburn, Indiana. The DIC Station is a specific ladle that will be used for the conversion of grey iron to ductile iron through the addition of a Magnesium treatment in a covered ladle. Therefore, the approval of this application will allow Auburn Foundry, Inc. Plant #1 to start producing ductile iron in addition to gray iron. Auburn Foundry, Inc. Plant #1 submitted a Part 70 application on May 31, 1996.

#### Stack Summary

Stack ID	Operation	Height (feet)	Diameter (feet)	Flow Rate (acfm)	Temperature (°F)
S-18	DIC Station	31	1.67	7,500	Ambient

#### Recommendation

The staff recommends to the Commissioner that the Part 70 Minor Source Modification be approved. This recommendation is based on the following facts and conditions:

Unless otherwise stated, information used in this review was derived from the application and additional information submitted by the applicant.

An application for the purposes of this review was received on May 19, 2003.

#### Emission Calculations

See Appendix A of this document for detailed emissions calculations (1 Page).

### Potential To Emit of Modification

Pursuant to 326 IAC 2-1.1-1(16), Potential to Emit is defined as “the maximum capacity of a stationary source to emit any air pollutant under its physical and operational design. Any physical or operational limitation on the capacity of a source to emit an air pollutant, including air pollution control equipment and restrictions on hours of operation or type or amount of material combusted, stored, or processed shall be treated as part of its design if the limitation is enforceable by the U. S. EPA.”

This table reflects the PTE before controls. Control equipment is not considered federally enforceable until it has been required in a federally enforceable permit.

Pollutant	Potential To Emit (tons/year)
PM	94.60
PM-10	94.60
SO <sub>2</sub>	0
VOC	0
CO	0
NO <sub>x</sub>	0

### Justification for Modification

The Part 70 Operating permit is being modified through a Part 70 Minor Source Modification. This modification is being performed pursuant to 326 IAC 2-7-10.5(d)(5)(C). The potential to emit is limited to less than twenty-five (25) tons per year by using a particulate air pollution control.

### County Attainment Status

The source is located in DeKalb County.

Pollutant	Status
PM-10	attainment
SO <sub>2</sub>	attainment
NO <sub>2</sub>	attainment
Ozone	attainment
CO	attainment
Lead	attainment

- (a) Volatile organic compounds (VOC) are precursors for the formation of ozone. Therefore, VOC emissions are considered when evaluating the rule applicability relating to the ozone standards. DeKalb County has been designated as attainment or unclassifiable for ozone. Therefore, VOC emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.
- (b) DeKalb County has been classified as attainment or unclassifiable for all other pollutants. Therefore, these emissions were reviewed pursuant to the requirements for Prevention of Significant Deterioration (PSD), 326 IAC 2-2.

### Source Status

Existing Source PSD or Emission Offset Definition (emissions after controls, based upon 8760 hours of operation per year at rated capacity and/or as otherwise limited):

Pollutant	Emissions (tons/year)
PM	Greater than 250
PM-10	Greater than 250
SO <sub>2</sub>	Greater than 250
VOC	Greater than 250
CO	Greater than 250
NO <sub>x</sub>	Greater than 100 but less than 250

- (a) This existing source is a major stationary source because an attainment regulated pollutant is emitted at a rate of 100 tons per year or more, and it is one of the 28 listed source categories.
- (b) These emissions are based upon previously issued permits.

#### Potential to Emit of Modification After Issuance

The table below summarizes the potential to emit, reflecting all limits, of the significant emission units after controls. The control equipment is considered federally enforceable only after issuance of this Part 70 source modification.

	Potential to Emit (tons/year)						
Process/facility	PM	PM-10	SO <sub>2</sub>	VOC	CO	NO <sub>x</sub>	HAPs
DIC station	0.95	0.95	0	0	0	0	0
PSD applicability levels	25	15	40	40	100	40	–

This modification to an existing major stationary source is not major because the emissions increase is less than the PSD significant levels. Therefore, pursuant to 326 IAC 2-2, the PSD requirements do not apply.

#### Federal Rule Applicability

- (a) There are no New Source Performance Standards (NSPS)(326 IAC 12 and 40 CFR Part 60) applicable to this proposed modification.
- (b) There are no National Emission Standards for Hazardous Air Pollutants (NESHAPs)(326 IAC 14 and 40 CFR Part 63) applicable to this proposed modification.

#### State Rule Applicability - Entire Source

##### 326 IAC 2-2 (Prevention of Significant Deterioration (PSD))

In order to render the requirements of 326 IAC 2-2 (PSD) not applicable to this modification, Auburn Foundry, Inc. accepted to limit the total melt rate of plant #1 to 208,463 tons per 12 consecutive month period with compliance determined at the end of each month. This limit is equivalent to the average melt rate for the period from September 1999 through August 2001. The limit on the plantwide melting rate will ensure that there will be no net increase in production

or actual emissions from the rest of the foundry processes as a result of this modification.

### State Rule Applicability - Individual Facilities

#### 326 IAC 2-7-10.5 Source Modifications

Pursuant to 326 IAC 2-7-10.5(d)(5)(C), the following conditions shall apply:

- (a) Baghouse BH-20 controlling the Ductile Iron Conversion (DIC) Station shall achieve and maintain ninety-nine percent (99%) control efficiency. In order to achieve this limit, the PM emission rate from the control device shall not exceed 0.216 pounds per hour.
- (b) Baghouse BH-20 controlling the Ductile Iron Conversion (DIC) Station shall comply with a no visible emission standard.
- (c) The potential to emit before controls shall not exceed major source thresholds for federal permitting programs.
- (d) The Permittee shall certify to the commissioner that the control device supplier guarantees that a specific outlet concentration, in conjunction with design air flow, will result in actual emissions less than twenty-five (25) tons of particulate matter (PM) or fifteen (15) tons per year of particulate matter with an aerodynamic diameter less than or equal to ten (10) micrometers (PM<sub>10</sub>).

#### 326 IAC 6-3-2 (Process Operations)

The particulate matter (PM) from the Ductile Iron Conversions (DIC) Station shall be limited by the following:

Interpolation of the data for the process weight rate up to sixty thousand (60,000) pounds per hour shall be accomplished by use of the equation:

$$E = 4.10 P^{0.67} \quad \text{where } E = \text{rate of emission in pounds per hour and} \\ P = \text{process weight rate in tons per hour}$$

$$E = 4.10(12)^{0.67} = 21.7 \text{ lb/hr}$$

Since the allowable level of emissions is greater than the uncontrolled potential to emit, the baghouse is not required to be in operation at all times the Ductile Iron Conversion (DIC) station is in operation in order to comply with this limit.

### Compliance Requirements

Permits issued under 326 IAC 2-7 are required to ensure that sources can demonstrate compliance with applicable state and federal rules on a more or less continuous basis. All state and federal rules contain compliance provisions, however, these provisions do not always fulfill the requirement for a more or less continuous demonstration. When this occurs IDEM, OAQ, in conjunction with the source, must develop specific conditions to satisfy 326 IAC 2-7-5. As a result, compliance requirements are divided into two sections: Compliance Determination Requirements and Compliance Monitoring Requirements.

Compliance Determination Requirements in Section D of the permit are those conditions that are found more or less directly within state and federal rules and the violation of which serves as grounds for enforcement action. If these conditions are not sufficient to demonstrate continuous compliance, they will be supplemented with Compliance Monitoring Requirements, also Section D of the permit. Unlike Compliance Determination Requirements, failure to meet Compliance Monitoring conditions would serve as a trigger for corrective actions and not grounds for enforcement action. However, a violation in relation to a compliance monitoring condition will

arise through a source's failure to take the appropriate corrective actions within a specific time period.

The compliance monitoring requirements applicable to this modification are as follows:

The Ductile Iron Conversions (DIC) Station has applicable compliance monitoring conditions as specified below:

(a) Visible Emissions Notations

- (1) Visible emission notations of the Ductile Iron Conversions (DIC) Station stack exhaust shall be performed once per shift during normal daylight operations when exhausting to the atmosphere. A trained employee shall record whether emissions are normal or abnormal.
- (2) For processes operated continuously, "normal" means those conditions prevailing, or expected to prevail, eighty percent (80%) of the time the process is in operation, not counting startup or shut down time.
- (3) In the case of batch or discontinuous operations, readings shall be taken during that part of the operation that would normally be expected to cause the greatest emissions.
- (4) A trained employee is an employee who has worked at the plant at least one (1) month and has been trained in the appearance and characteristics of normal visible emissions for that specific process.
- (5) The Compliance Response Plan for this unit shall contain troubleshooting contingency and response steps for when an abnormal emission is observed. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

(b) Parametric Monitoring

The Permittee shall record the total static pressure drop across the baghouse used in conjunction with the Ductile Iron Conversions (DIC) Station, at least once per shift when the Ductile Iron Conversions (DIC) Station is in operation. When for any one reading, the pressure drop across the baghouse is outside the normal range of 3.0 and 6.0 inches of water or a range established during the latest stack test, the Permittee shall take reasonable response steps in accordance with Section C- Compliance Response Plan - Preparation, Implementation, Records, and Reports. A pressure reading that is outside the above mentioned range is not a deviation from this permit. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.

The instrument used for determining the pressure shall comply with Section C - Pressure Gauge and Other Instrument Specifications, of this permit, shall be subject to approval by IDEM, OAQ and shall be calibrated at least once every six (6) months.

(c) Baghouse Inspections

An inspection shall be performed each calendar quarter of all bags controlling the Ductile Iron Conversions (DIC) Station when venting to the atmosphere. Inspections required by this condition shall not be performed in consecutive months. All defective bags shall be replaced.

(d) Broken or Failed Bag Detection

In the event that bag failure has been observed:

- (1) For multi-compartment units, the affected compartments will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if there are no visible emissions or if the event qualifies as an emergency and the Permittee satisfies the emergency provisions of this permit (Section B- Emergency Provisions). Within eight (8) business hours of the determination of failure, response steps according to the timetable described in the Compliance Response Plan shall be initiated. For any failure with corresponding response steps and timetable not described in the Compliance Response Plan, response steps shall be devised within eight (8) business hours of discovery of the failure and shall include a timetable for completion. Failure to take response steps in accordance with Section C - Compliance Response Plan - Preparation, Implementation, Records, and Reports, shall be considered a violation of this permit.
- (2) For single compartment baghouses, if failure is indicated by a significant drop in the baghouse's pressure readings with abnormal visible emissions or the failure is indicated by an opacity violation, or if bag failure is determined by other means, such as gas temperatures, flow rates, air infiltration, leaks, dust traces or triboflows, then failed units and the associated process will be shut down immediately until the failed units have been repaired or replaced. Operations may continue only if the event qualifies as an emergency and the Permittee satisfies the requirements of the emergency provisions of this permit (Section B - Emergency Provisions).

These monitoring conditions are necessary because the baghouse for the Ductile Iron Conversions (DIC) Station must operate properly to ensure compliance with 326 IAC 2-7-10.5(d)(5)(C).

## **Conclusion**

The construction of this proposed modification shall be subject to the conditions of the attached proposed Part 70 Minor Source Modification No. 033-17306-00002.



Auburn Foundry, Inc  
Auburn, Indiana  
Ghassan Shalabi  
033-17306-00002

Page 1 of 1

#### Ductile Iron Conversion (DIC) Station

Capacity	12	tons of metal/hour
EF	1.8	pounds/ton of metal
Emissions	21.6	pounds/hour
	94.608	tons/year

#### Emissions after control

Control Efficiency	99%		
Emissions	0.946 tons/year =	0.216 lb/hr	limit in condition D.1.1(a)

Control device is guaranteed to meet	0.005 gr/dscf	PM/PM10
--------------------------------------	---------------	---------

Guaranteed PM/PM10 emissions	1.314 tons/yr < 25 tpy PM and 15 tpy PM10
	Limit in condition (D.1.1(d))